

RSP200D

200W Monocrystalline Solar Panel

Key Features

The Renogy 200W solar panels offer more power and durability. Corrosion-resistant aluminum frame. Larger cell size and conversion efficiency for more power output per surface area.

- High module conversion efficiency
- Top ranked PTC rating
- Quick and inexpensive mounting
- 100% EL testing on all Renogy modules
- No hot spots guaranteed

Potential Uses

The Renogy 200W Monocrystalline Solar Panel has applications in off-grid power systems. That includes 12 and 24 volts battery banks, water pumping systems, signaling systems, and other off-grid applications.



Power Output Warranty



Material and Workmanship Warranty

RSP200D

200W Monocrystalline Solar Panel

Electrical Data

Maximum Power at STC*	200 W
Optimum Operating Voltage (V _{mp})	19.2 V
Optimum Operating Current (Imp)	10.42 A
Open Circuit Voltage (V _{oc})	23.0 V
Short Circuit Current (I _{sc})	11.05 A
Module Efficiency	19.2%
Maximum System Voltage	600 VDC
Maximum Series Fuse Rating	20 A

Thermal Characteristics

OperatingTemp. Range	-40°C - 85°C(-40°F - 185°I	F)
Nominal Operating Cell Ten	nerature (NOCT) 47±2°	С
Temperature Coefficient of F	Pmax -0.37%/º	С
Temperature Coefficient of V	Voc -0.28%/°	С
Temperature Coefficient of I	lsc 0.05%/°	С

Junction Box

IP Rating	IP 65
Diode Type	20SQ045
Number of Diodes	2 Diode(s)
Output Cables	14 AWG 800mm (31.5 in)

Solar Cell Type	Monocrystalline (6.5 x 3.3 in)
Number of Cells	68 (4 x 17)
Dimensions	1491 x 699 x 35 mm (58.7 x 27.5 x 1.4 in)
Weight	12 kg (26.5 lbs)
Front Glass	Tempered Glass 0.13 in (3.2 mm)
Frame	Anodized Aluminum Alloy
Connectors	MC4 Connectors
Fire Performand	te Type 1

MC4 Connectors

Mechanical Data

Rated Current	30 A
Maximum Voltage	1000 VDC
Maximum AWG Size Range	12 AWG
Temperature Range	-40°C -90°C(-40°F - 194°F)
IP Rating	IP 68

Certifications




IV-Curve






Module Diagram



RSP200D Characteristics Versus Voltage



^{*+}All specifications and data described in this data sheet are tested under Standard Test Conditions (STC - Irradiance: 1000W/m², Temperature: 25°C, Air Mass: 1.5) and may deviate marginally from actual values. Renogy and any of its affiliates has reserved the right to make any modifications to the information on this data sheet without notice. It is our goal to supply our customers with the most recent information regarding our products. These data sheets can be found in the downloads section of our website, www.renogy.com